



Certificate of Conformity

Certificate number: CM40321

Certification Body:


ABN: 80 111 217 568
JAS-ANZ Accreditation
No. Z4450210AK
PO Box 7144, Sippy
Downs Qld 4556
+61 (07) 5445 2199
www.CertMark.org

Certificate Holder:


Waterproofing, Flooring & Concrete Repair Industries
Bayset
ABN: 27066428877
Unit 1, 76 Postle St,
Coopers Plains,
Qld 4108
Ph: (07) 3722 3822
W: www.bayset.com.au

THIS IS TO CERTIFY THAT

WPA Aqualay External Above Ground Waterproofing Membrane

Type and/or use of product:

External Use Above Ground Waterproofing Membrane.

Description of product:

Waterproofing membrane WPA Aqualay is for use in external above ground applications. Refer A2.

COMPLIES WITH THE FOLLOWING BCA PROVISIONS AND STATE OR TERRITORY VARIATION(S)

BCA 2019 (Amdt. 1)

	Volume One	Volume Two
Performance Requirement(s):	Not Applicable	Not Applicable
Deemed-to-Satisfy Provision(s):	F1.4 Damp and weatherproofing - External above ground membranes	3.8.1.3 Wet areas and external waterproofing - External above ground membranes
State or territory variation(s):	Not Applicable	Not Applicable

SUBJECT TO THE FOLLOWING LIMITATIONS AND CONDITIONS AND THE PRODUCT TECHNICAL DATA IN APPENDIX A AND EVALUATION STATEMENTS IN APPENDIX B

Limitations and conditions:

- Where required by the Appropriate Authority, installation must be undertaken by a person holding the required State or Territory licensing or registration.
- The WPA Aqualay External Above Ground Waterproofing Membrane must be installed with the [WPA Aqualay Data Sheet 032022](#).
- Do not apply WPA AQUALAY:
 - If it is raining or if rain is imminent;
 - Over contaminated substrate;
 - Not compatible with solvent based materials, e.g. adhesives, sealants or coatings;
 - As an exposed membrane system, must be covered and protected by screeds, tiles or stone;
 - In areas subject to vehicular traffic;
 - Do not apply when surface temperature is below 5°C or above 30°C; or
 - To areas of continuous immersion such as swimming pools, ponds, water features or water tanks.
- Particle board flooring is not suitable as a substrate for WPA Aqualay External Above Ground Waterproofing Membrane.
- The use of the certified product/system is subject to these Limitations and Conditions and must be read in conjunction with the Scope of Certification below.

Building classification/s:

Class 1,2,3,4,5,6,7,8,9 & 10


Richard Donarski - CMI


Don Grehan – Unrestricted Building Certifier

Date of issue: 05/04/2022

Date of expiry: 05/04/2025





Certificate of Conformity

Scope of certification: The CodeMark Scheme is a building product certification scheme. The rules of the Scheme are available at the ABCB website www.abcb.gov.au. This Certificate of Conformity is to confirm that the relevant requirements of the Building Code of Australia (BCA) as claimed against have been met. The responsibility for the product performance and its fitness for the intended use remain with the Certificate Holder. The certification is not transferrable to a manufacturer not listed on Appendix A of this certificate.

Only criteria as identified within this Certificate of Conformity can be used for CodeMark certification claims. Where other claims are made in a client's Installation Manual, Website or other documents that are outside the criteria on this Certificate of Conformity, such criteria cannot be used or claimed to meet the requirements of this CodeMark certification.

The NCC defines a Performance Solution as one that complies with the Performance Requirements by means other than a Deemed-to-Satisfy Solution. A Building Solution that relies on a CodeMark Certificate of Conformity that certifies a product against the Performance Requirements cannot be considered as Deemed-to-Satisfy Solution.

This Certificate of Conformity may only relate to a part of a Performance Solution. In these circumstances other evidence of suitability is needed to demonstrate that the relevant Performance Requirements have been met. The relevant provisions of the Governing Requirements in Part A of the NCC will also need to be satisfied.

This Certificate of Conformity is issued based on the evidence of compliance as detailed herein. Any deviation from the specifications contained in this Certificate of Conformity is outside of this document's scope and the installation of the certified product will not be covered by this Certificate of Conformity.

Disclaimer: The Scheme Owner, Scheme Administrator and Scheme Accreditation Body do not make any representations, warranties or guarantees, and accept no legal liability whatsoever arising from or connected to, the accuracy, reliability, currency or completeness of any material contained within this certificate; and the Scheme Owner, Scheme Administrator and Scheme Accreditation Body disclaim to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this certificate.

When using the CodeMark logo in relation to or on the product/system, the Certificate Holder makes a declaration of compliance with the Scope of Certification and confirms that the product is identical to the product certified herein. In issuing this Certificate of Conformity, CertMark International has relied on the experience and expertise of external bodies (laboratories and technical experts).

Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.

APPENDIX A – PRODUCT TECHNICAL DATA

A1 Type and intended use of product

The WPA Aqualay External Above Ground Waterproofing Membrane is suitable for application onto concrete & masonry block work, Screeds and renders, Wet area grade plasterboard, CFC and fibre cement sheeting, PAA structural and marine plywood &, Autoclaved aerated concrete panels (AAC).

A2 Description of product

WPA Aqualay is a 0.57mm thick sheet membrane consisting of an EVAC core with a laminated non-woven geotextile fleece on either side of the central core.

A3 Product specification

The WPA Aqualay External Above Ground Waterproofing Membrane meets the requirements of a Class II, medium extensibility membrane, when tested in accordance with the requirements of AS/NZS 4858:2004(R2020), and when the product thickness is ~0.57mm on concrete, plywood, fibre cement, particleboard, and plasterboard substrates.

A4 Manufacturer and manufacturing plant(s)

This field is voluntary. Contact Certificate Holder for details.

A5 Installation requirements

The WPA Aqualay External Above Ground Waterproofing Membrane must be installed with the [WPA Aqualay Data Sheet 032022](#).

A6 Other relevant technical data

No other relevant technical data.

APPENDIX B – EVALUATION STATEMENTS

B1 Evaluation methods

1. Damp and Weatherproofing Provision A5.2(1)(e). Reports from Appropriately Qualified Person.

B2 Reports

1. BRANZ; Report No. DC13066-004; Report on Bayset WPA Aqualay Membrane meeting the Deemed-To-Satisfy Provisions of the NCC 2019 Amendment 1; Dated 20/04/2021.

The Certificate Holder has chosen not to make the above evidence of compliance publicly available, due to the documents being considered commercial in confidence.